

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Substance
Substance name	: Acetone
Chemical name	: acetone; propan-2-one; propanone
IUPAC name	: Unnamed
EC Index-No.	: 606-001-00-8
EC-No.	: 200-662-2
CAS-No.	: 67-64-1
REACH registration No	: 01-2119471330-49
Product code	: ACETGEN
Type of product	: Solvents

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public	
Main use category	: Industrial use, Professional use
Use of the substance/mixture	: Blowing agents - Industrial Manufacture;, Distribution of substance and Mixtures - Industrial Mining chemicals - Industrial Manufacture of Polymers. - Industrial Polymer processing - Industrial Rubber production and processing - Industrial Use as binders and release agents - Industrial Use in laboratories - Industrial Use in Cleaning Agents - Industrial Uses in Coatings - Industrial Use in Oil and Gas field drilling and production operations - Industrial Use in Agrochemicals - Professional De-icing and anti-icing applications - Professional Explosives manufacture and use - Professional Manufacture of Polymers. - Professional Polymer processing - Professional Use as binders and release agents - Professional Use in laboratories - Professional Use in Cleaning Agents - Professional Uses in Coatings - Professional Use in Oil and Gas field drilling and production operations – Professional De-icing and anti-icing applications - Consumer Use in Cleaning Agents - Consumer Uses in Coatings - Consumer
Use of the substance/mixture	: Solvents

1.2.2. Uses advised against

Restrictions on use	: Not Otherwise Specified
---------------------	---------------------------

1.3. Details of the supplier of the safety data sheet**Supplier**

J.V. Barrett & Co. Ltd
St Ivel Way
Warmley
BS30 8TY Bristol - United Kingdom
T +44 (0)1179 60 00 60
sales@barrettine.co.uk - www.barrettine.co.uk

EU

Barrettine (Europe) Ltd
Unit 3D North Point House, North Point Business Park,
New Mallow Road
T23 AT2P Cork - Ireland
T +44 1179 60 00 60
sales@barrettine.co.uk - www.barrettine.co.uk

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1.4. Emergency telephone number

Emergency number : +44 (0) 1179 600060 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm Fri.)
+44 (0) 1270 502891 (Out of hours emergency number)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing vapours, spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective gloves.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening :

Not applicable

Tactile warning :

Applicable

2.3. Other hazards

No additional information available

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray, vapours, mist, fume. Avoid contact with skin and eyes.

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorised site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, mist, vapours, spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m ³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acetone (67-64-1)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt

PNEC (Soil)

PNEC soil	29.5 mg/kg dwt
-----------	----------------

PNEC (STP)

PNEC sewage treatment plant	100 mg/l
-----------------------------	----------

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Materials for protective clothing:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
In case of contact through splashing, Repeated or prolonged exposure	Butyl rubber	5 (> 240 minutes)	0.5		

Eye protection:

Safety glasses. Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Respiratory protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Device	Filter type	Condition	Standard
Full face mask, Aerosol mask, Disposable half mask	Filter AX (brown), Type P3	Vapour protection	

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Molecular mass	: 58.08 g/mol Source: pubchem
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -94.8 °C
Freezing point	: No data available
Boiling point	: 56.05 °C
Flash point	: -17 °C
Auto-ignition temperature	: 465 °C Source: ICSC
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 24 mm Hg 25°C Source: ICSC
Relative vapour density at 20 °C	: 2 Source: HSDB
Relative density	: 0.8 Source: ICSC
Solubility	: completely miscible.
Partition coefficient n-octanol/water (Log Pow)	: -0.24 Source: ICSC
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.32 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Upper explosive limit (UEL)	: 2.2 – 13 % Source: ICSC

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Acetone (67-64-1)

LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified
Not rapidly degradable

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acetone (67-64-1)

LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Acetone (67-64-1)

Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
---	--------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1090	UN 1090	UN 1090	UN 1090	UN 1090
14.2. UN proper shipping name				
ACETONE	ACETONE	Acetone	ACETONE	ACETONE
Transport document description				
UN 1090 ACETONE, 3, II, (D/E)	UN 1090 ACETONE, 3, II (-20°C c.c.)	UN 1090 Acetone, 3, II	UN 1090 ACETONE, 3, II	UN 1090 ACETONE, 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:

33

1090

Tunnel restriction code (ADR)	: D/E
EAC code	: •2YE

Transport by sea

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: E
Flash point (IMDG)	: -20°C to -18°C c.c.
Properties and observations (IMDG)	: Colourless, clear liquid, with a characteristic mint-like odour. Flashpoint: -20°C to -18°C c.c. Explosive limits: 2.5% to 13% Miscible with water.

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3H

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3(a)	Acetone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Acetone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
40.	Acetone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Acetone is not on the REACH Candidate List

Acetone is not on the REACH Annex XIV List

Organic solvent

Acetone is subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Acetone is not subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
List entry in the directive:: FLAMMABLE LIQUIDS; P5c
Qualifying quantity 1: 5,000 t; Qualifying quantity 2: 50,000 t;

15.1.2. National regulations

Listed on ELINCS (European List of Notified Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Indication of changes:

New format.

Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes version of	Modified	
1.3	Additional information	Added	
1.4	Additional information	Added	
15	Additional information	Added	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)

Acetone

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

The classification complies with : ATP 12

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.