

## Fibreglass Tape – GS1053 (200g/m<sup>2</sup>)

### Description

Textile Technologies GS1053 is woven from a special type of silane resin compatible glass yarn resistant to oils, solvents and most chemicals. GS1053 becomes quickly saturated with resins, leaving a pliable matting easily moulded into the required shape.

### Features

- Quickly saturates with resin
- Easily moulds to shape
- Various weaves available
- Widths to 300mm
- Wide range of other weights / m<sup>2</sup> available



### Applications

GS1053 can be applied as reinforcements for a wide variety of GRP applications - mouldings, small GRP components, Boat Building, prevention and repair of reflective cracking on highways, wind turbine blade construction.

### Technical

Yarn Type	E Glass Fibre Yarn
Reference	GS1053 Range
Weight	200g/m <sup>2</sup>
Warp	EC9 136 Tex (Silane Resin Compatible)
Weft	EC9 08 Tex (Silane Resin Compatible)
Weaving Direction	0 degrees x 90 degrees (Plain)
Weaving Width	25mm - 300mm
Roll Length	50 metres
Thickness	0.25mm +/-0.5mm

### Products

Product	Width	Roll Length	Packed in
GS1053/12.5/30	12.5mm	50m	20's
GS1053/25/30	25mm	50m	10's
GS1053/50/30	50mm	50m	6's
GS1053/75/30	75mm	50m	4's
GS1053/100/30	100mm	50m	3's
GS1053/150/30	150mm	50m	2's
GS1053/200/30	200mm	50m	2's
GS1053/300/30	300mm	50m	1's